

ABLOY® PROTEC²

TUBULAR DEADBOLTS



ABLOY® PROTEC²



STANDARD BOLT
ABLOY® LC801

DRIVE-IN BOLT
ABLOY® LC802




A 2 3/8 (60 mm) or 2 3/4 (70 mm)
(Adjustable)

A 2 3/8 (60 mm) or 2 3/4 (70 mm)
(Adjustable)

CY411T
DOUBLE CYLINDER

ME151
c/LC801

ME152
c/LC802



Bolt operated by key outside and inside.

SECURITY FEATURES

- UL listed products
 - UL Burglary
 - UL 20 min fire rating
- Case hardened steel cylinder housing
- Rotating collar
- Optional key lockable thumbturn
- 6 mm steel retaining screws
- High security bolt
 - hardened steel with 2" length
 - 1" (25,4 mm) throw
- Reinforced steel strike box
- Protective bolt shield

CY412T
SINGLE CYLINDER
WITH THUMBTURN

ME153
c/LC801

ME154
c/LC802



Bolt operated by key outside and thumbturn inside.

STANDARD FINISHES



US26/625
Bright Chrome



US26D/626
Satin Chrome



US3/605
Bright Brass PVD



US4/606
Satin Brass

CY413T
SINGLE CYLINDER
WITH KEY LOCKABLE
THUMBTURN

ME155
c/LC801

ME156
c/LC802



Bolt operated by key outside and thumbturn inside.
Inside thumbturn can be locked with proper key to provide double cylinder security.

Fits 1 3/4" (44,5 mm) to 2 1/8" (54 mm) hole. Standard hardware for 1 3/4" (44,5 mm) thick door included.



www.abloy.com

Abloy Oy
Wahlforssinkatu 20
P.O.Box 108
FI-80101 JOENSUU
FINLAND
Tel. +358 20 599 2501
Fax +358 20 599 2209



An ASSA ABLOY Group brand

Abloy Oy is one of the leading manufacturers of locks, locking systems and architectural hardware and the world's leading developer of products in the field of electromechanical locking technology.

ASSA ABLOY is the global leader in door opening solutions, dedicated to satisfying end-user needs for security, safety and convenience.

ASSA ABLOY